

IN THE CLAIMS

Sub  
D1

1. (currently amended) A driver circuit for a display device comprising: means for storing a basic setting of an adjustable characteristic of the driver circuit, characterized in that the driver circuit includes means for storing a correction factor to correct the basic setting of the adjustable characteristic of the driver circuit, and in that the driver circuit is operative to adjust the adjustable characteristic based on the combined effect of both the basic setting and the correction factor.

cl  
cont

2. (previously amended) A driver circuit as claimed in claim 1, characterized in that the means for storing a correction factor to correct the basic setting of the adjustable driver characteristic is accessible.

3. (previously amended) A driver circuit as claimed in claim 1, characterized in that the means for storing the basic setting of an adjustable driver characteristic is of the PROM type.

4. (previously amended) A driver circuit as claimed in claim 1, characterized in that the correction factor which enables the driver circuit to correct the basic setting of the adjustable characteristic of the driver circuit has a substantially smaller

adjustment range than the basic setting of the adjustable characteristic of the driver circuit.

5. (currently amended) A display module comprising:  
the ~~display-driver circuit~~ circuit as claimed in claim 1, and a particular  
display device connected to the ~~display-driver circuit~~,  
characterized in that the correction factor in the means for storing  
a correction factor is based on an individual property of the  
particular display device.

*Ch  
one*  
6. (previously amended) A method of adjusting an individual  
property of a display module containing a display device and a  
driver circuit connected to said display device, characterized in  
that the method includes the following steps  
determining a basic setting based on expected characteristics of the  
display device and characteristics of the driver circuit,  
storing the determined basic setting to be used by the driver  
circuit,  
determining a correction factor to the basic setting based on the  
actual characteristic of the display device and the characteristics  
of the driver circuit when the basic setting is used, and storing  
the correction factor to be used by the driver circuit.

7. (currently amended) A method as claimed in claim 6 further comprising:

adjusting the driver circuit based upon the combination of both the stored basic setting and the stored correction factor thereby to adjust the display module.

8. (previously added) A method as claimed in claim 7 further comprising:

determining the ambient temperature in which the display module is operated, and wherein

the driver circuit is adjusted based upon the stored basic setting, the stored correction factor and the determined ambient temperature.

9. (currently amended) A driver circuit as claimed in claim 1 further comprising:

means for deriving a temperature correction factor determined by the ambient temperature in which the display device is operated, and

means for generating a drive signal for the display device in response to the adjustable characteristic which simultaneously is based upon the stored basic setting, the stored correction factor and the temperature correction factor.

10. (currently amended) A driver circuit for a display device comprising:

means for storing a basic setting of an adjustable characteristic of the driver circuit,

means for storing a correction factor to correct the basic setting of the adjustable characteristic of the driver circuit, and

means for generating a ~~driver~~ drive signal for the display device that is determined by ~~both~~ the stored basic setting and as modified by the stored correction factor.

11. (previously added) A driver circuit as claimed in claim 10 further comprising means for deriving the correction factor by a calibration operation based upon measurement of the optical quality of the display device.

12. (currently amended) A driver circuit as claimed in claim 10 wherein the basic setting is based upon at least one of, the spread in the manufacturing process of the ~~drive~~ driver circuit, and a typical temperature dependence of a typical display device.

13. (previously added) A driver circuit as claimed in claim 10 wherein the correction factor is based upon a particular model of display devices, all of which are then operable with the driver

circuit and without adjustment of the contrast of the display device by a user thereof.

14. (previously added) A driver circuit as claimed in claim 10 wherein neither the stored basic setting or the stored correction factor are temperature dependent parameters.

15. (currently amended) A method as claimed in claim 6 wherein the stored basic setting and the stored correction factor are each independent of ambient temperature of the display module.

16. (previously added) A method as claimed in claim 6 wherein the stored correction factor is derived by a calibration procedure based upon measuring the optical quality of the display module.

17. (previously added) A method as claimed in claim 6 which further comprises:

deriving an output signal of the driver circuit based upon both the stored basic setting and the stored correction factor.